




# MNT BEARING LTD



## 55 mm x 72 mm x 9 mm SKF 61811 Ball bearing

Bearing No. 61811

Size	72x55x9 mm
Bore Diameter	72 mm
Outer Diameter	55 mm
Width	9 mm
d	55 mm
D	72 mm
B	9 mm
d <sub>1</sub>	60.6 mm
D <sub>1</sub>	66.4 mm
r <sub>1,2</sub> - min.	0.3 mm
d <sub>a</sub> - min.	57 mm
D <sub>a</sub> - max.	70 mm
r <sub>a</sub> - max.	0.3 mm
Basic dynamic load rating - C	9 kN
Basic static load rating - C <sub>0</sub>	8.8 kN
Fatigue load limit - P <sub>u</sub>	0.375 kN
Reference speed	19000 r/min
Limiting speed	12000 r/min
Calculation factor - k <sub>r</sub>	0.015
Calculation factor - f <sub>0</sub>	17
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.093

61811 Bearing 2D drawings and 3D CAD models



## MNT BEARING LTD

Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	55MM Bore; 72MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.skf.com">http://www.skf.com</a>
Manufacturer Item Number	61811
Weight / LBS	0.2
Outside Diameter	2.835 Inch   72 Millimeter
Outer Race Width	0.354 Inch   9 Millimeter
Bore	2.165 Inch   55 Millimeter
bore diameter:	55 mm
static load capacity:	8.8 kN
outside diameter:	72 mm
precision rating:	Not Rated
overall width:	9 mm



## MNT BEARING LTD

finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	9 mm
row type & fill slot:	Single Row Non-Fill Slot
fillet radius:	0.3 mm
snap ring included:	Without Snap Ring
maximum rpm:	12000 RPM
internal clearance:	C0
series:	61
dynamic load capacity:	9.04 kN
$d_1$	60.3 mm
$D_1$	67 mm
$r_{1,2}$ min.	0.3 mm
$d_a$ min.	57 mm
$D_a$ max.	70 mm
$r_a$ max.	0.3 mm
Basic dynamic load rating C	9.04 kN
Basic static load rating $C_0$	8.8 kN
Fatigue load limit $P_u$	0.375 kN
Calculation factor $k_r$	0.015
Calculation factor $f_0$	17
Mass bearing	0.083 kg