



# MNT BEARING LTD

## 6HR1530+[70-1600/1]L[H,P,SP,UP][F(A P-C),F(AP-CF),F(AP-HC)] THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 6HR1530+[70-1600/1]L[H,P,SP,UP][F(AP-  
C),F(AP-CF),F(AP-HC)]

6HR1530+[70-1600/1]L[H,P,SP,UP][F(AP-  
C),F(AP-CF),F(AP-HC)] Bearing 2D drawings  
and 3D CAD models

Days to Ship	42 Days
Rail Width W1	10.7 mm
Mounting Height M	15 mm
Number of blocks	6
Material	Carbon Steel
Rail Length L	70 ~ 1600 mm
Accuracy Grade	High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	1530
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	4310
Basic Load Rating Static Rating Co(N)	7650
Allowable static moment MA(N · m)	98.2
Allowable static moment MB(N · m)	98.2
The outside dimension W of block	19.2 mm
The outside dimension L of block	69 mm
Mounting Hole Dimension S(M)	M4



## MNT BEARING LTD

The dimension L1 of bocks	40 mm
LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Industrial Black Chrome Coating / Industrial Black Chrome Film Treated - Special Fluororesin Coating / Industrial Hard Chrome Plating