



MNT BEARING LTD

6HR3065T+[175-3000/1]L[F(AP-C),F(AP-CF),F(AP-HC)] THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 6HR3065T+[175-3000/1]L[F(AP-C),F(AP-CF),F(AP-HC)]

6HR3065T+[175-3000/1]L[F(AP-C),F(AP-CF),F(AP-HC)] Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Rail Width W1	25 mm
Mounting Height M	30 mm
Number of blocks	6
Material	Carbon Steel
Rail Length L	175 ~ 3000 mm
Accuracy Grade	Standard Grade
Callout Size	3065
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	32100
Basic Load Rating Static Rating Co(N)	51600
Allowable static moment MA(N · m)	1890
Allowable static moment MB(N · m)	1890
The outside dimension W of block	40.3 mm
The outside dimension L of block	173.5 mm
Mounting Hole Dimension S(M)	M10
The dimension L1 of bocks	118.5 mm
LM Block Surface Treatment (* Surface treatment that differs	Not Provided



MNT BEARING LTD

between the rail and block or only on the rail or block is not available.)	
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Industrial Black Chrome Coating / Industrial Black Chrome Film Treated - Special Fluororesin Coating / Industrial Hard Chrome Plating