



MNT BEARING LTD

6HR3575T[F(AP-C),F(AP-CF),F(AP-HC)]+[184-3000/1]L[H,P,SP,UP] THK Separated Linear Guide Side Rails Set Model HR

Bearing No. 6HR3575T[F(AP-C),F(AP-CF),F(AP-HC)]+[184-3000/1]L[H,P,SP,UP]

6HR3575T[F(AP-C),F(AP-CF),F(AP-HC)]+[184-3000/1]L[H,P,SP,UP] Bearing 2D drawings and 3D CAD models

Days to Ship	42 Days
Rail Width W1	30.5 mm
Mounting Height M	35 mm
Number of blocks	6
Material	Carbon Steel
Rail Length L	184 ~ 3000 mm
Accuracy Grade	High Grade / Precision Grade / High Precision Grade / Extra High Precision Grade
Callout Size	3575
Rolling Element	Ball
Basic Load Rating Dynamic Rating C(N)	40200
Basic Load Rating Static Rating Co(N)	63600
Allowable static moment MA(N · m)	2590
Allowable static moment MB(N · m)	2590
The outside dimension W of block	44.9 mm
The outside dimension L of block	182.5 mm
Mounting Hole Dimension S(M)	M12
The dimension L1 of blocks	131.5 mm



MNT BEARING LTD

LM Block Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Industrial Black Chrome Coating / Industrial Black Chrome Film Treated - Special Fluororesin Coating / Industrial Hard Chrome Plating
LM Rail Surface Treatment (* Surface treatment that differs between the rail and block or only on the rail or block is not available.)	Not Provided